

JANUS FILTERS HOUSINGS

10" & 5" Slimline Plastic Housings

Polypropylene

8.6 Bar

52 °C

Housing Options

Shown with pressure release button

10"



3G head with integral bracket



3G head with meter mount

5"



Pressure release button

| PRODUCT CODE | DESCRIPTION |
|---------------------------|---|
| Blue Housings | |
| NO5SLBL1/2"W/PRBT | No.5 Slimline blue, 1/2", with pressure release |
| NO5SLBL1/2"WO/PRBT | No.5 Slimline blue, 1/2", without pressure release |
| NO103GSTBK/BL3/4"BTIBW/PR | No.10 3G blue, 3/4", integral bracket, with pressure release |
| NO103GSTBK/BL3/4"BTMMW/PR | No.10 3G blue, 3/4", integral bracket, meter mount, with pressure release |



Flow Rates

When using these housings with the type of cartridge below, the following flow rates can be achieved:

| CARTRIDGE TYPE | MAX FLOW RATE (IPM) |
|----------------|---------------------|
| Pleated | 28 |
| Depth | 16 |
| Carbon | 1.9 |

Figures based on 1µm cartridge at 1psi Δp



| PRODUCT CODE | DESCRIPTION |
|-----------------------------|------------------|
| Pressure Accessories | |
| PD1 | Gauge - 2 Colour |
| PD2 | Gauge - 3 Colour |

The Water Hydraulics Co. Ltd.

Alexandra House, English Street, Hull, East Yorkshire, HU3 2DJ, United Kingdom.

Tel: +44 (0)1482 595000, E-Mail: sales@waterhydraulics.co.uk.

England Website: www.waterhydraulics.co.uk



FM 87247

Whilst every endeavour has been made to ensure accuracy, this publication cannot be considered to represent